

SEM10-F Amada

TFT-monitor 10,4"



Overview:

- 10,4" TFT / LCD monitor for AMADA APX100 and operateur OPC8XA
- replacement for 12" CRT (colour)
- interface HD-SUB15 or 10pin connector
- Input frequencies form 15 kHz / 50Hz
- Settings via on-screen-menu
- long-term availability

Description:

Monitors SEM10-F are used as replacement for CRT-monitors in controls Operateur OPC8XA and APX100 from AMADA. The default timing is compatible to the control, this means after connecting the monitor the visualisation works correctly. Further adjustments can be made via on-screen-menu. The connector and interface for the graphic-signal are compatible to the control, so the replacement is easy. Mounting via mounting angles on the existing frontpanel, so fast and simple replacement is possible with no specialized knowledge.

Technical Data:

Overview:

Industrial TFT monitor 10,4" for mounting in controlpanel

Control:

opérateur OPC8XA, Amada APX100

Interfaces:

HD-SUB15 or 10pin connector

Synchronisation / Timings:

compatible to control

Resolution:

max. 800x600

Visible picture:

216x136mm

Adjustments:

via on-screen-menu

Brightness / Contrast:

min. 250 cd/qm, 500:1

Power supply:

115/230 VAC

MTBF:

Backlights min. 50000h

Mechanical dimensions:

frontpanel: about 483 x 266mm

Material:

Aluminium

environmental conditions:

operating temperature: 0-50°C

storage temperature: 0-65°C

humidity: 10 - 80 % rel. humidity, not condensing

norms:

EMV: EN55022 EN55024; EN61010-1

part number:

10030863 SEM10-F Amada