SEM10-F Deckel Multiform 4

Replacement 10"





Overview

- TFT / LCD monitor for Deckel Multiform 4
- Interface HD-SUB15/ 5xBNC and 3x adapter BNC to mini-Koax femaile
- Connector and signal timing compatible to the control
- Settings via on-screen-menu
- Long-term availability
- Frontpanel black with holes for mounting

Description

The monitors SEM10-F are used as replacement for 12" CRT-monitors monochrome for control multiform 4 of Deckel.

The default timing is compatible to the control, this means after connecting the monitor the visualisation works correctly. Further adjustments can be made via on-screen-menu. Connector and interface for graphic-signal are compatible to the control, so the replacement is easy. Fast and simple replacement in the cutout of the old crt- monitor without any specialized knowledge.

Technical data

Overview:

Industry TFT monitor 10" for Decekl

Control:

Multiform 4

Original monitor:

12" CRT-monitor monochrome

Interfaces:

D-Sub 9 female, HD-SUB15 female

Synchronisation / Timings:

kompatibel zur Steuerung

Resolution:

max. 1024x768

Visible picture:

211x158mm

Adjustments:

via on-screen-menu

Brightness / Contrast:

min. 500 cd/gm, 1000:1

Power supply:

115/230VAC

MTBF:

Backlights min. 50000h

Mechanical dimension:

Case: 260 x 190 x 55 (95)mm Frontpanel: 267 x 197 x 3mm cutout: min 256 x 186 mm

Material:

Frontpanel: aluminium powder-coated black

Protective glass

Environmental conditions:

Operating temperature 0-50°C Storage temperature 0-65°C

Humidity: 10 - 80 % rel. humidity, not condensing

Protection class:

Front IP 65

Norms

EN55022 EN55024 EN61010-1

Part number

10030683 SEM10-F-Deckel multiform 4