

SEM12-F Deckel Multiform 3

Replacement 12"



Overview

- TFT / LCD monitor for Deckel Multiform 3
- replacement for 14" CRT
- Interface HD-SUB15/ 5xBNC and 3x adapter BNC to mini-Koax female
- Connector and signal timing compatible to the control
- Settings via on-screen-menu
- Long-term availability

Description

The monitors SEM12-F are used as replacement for 14" CRT-monitors for control multiform 3 of Deckel. The default timing is compatible to the control, this means after connecting the monitor the visualisation works correctly. Further adjustments can be made via on-screen-menu. Connector and interface for graphic-signal are compatible to the control, so the replacement is easy. Fast and simple replacement in the cutout of the old crt- monitor without any specialized knowledge.

Technical data

Overview:

Industry TFT monitor 12" for Deckel

Control:

Multiform 3

Original monitor:

14" CRT-monitor

Interfaces:

HD-Sub 15, 5xBNC and 3x adapter BNC to mini-Koax female

Synchronisation / Timings:

kompatibel zur Steuerung

Resolution:

max. 800x600

Visible picture:

246x185mm

Adjustments:

via on-screen-menu

Brightness / Contrast:

min. 400 cd/qm, 500:1

Power supply:

115/230VAC

MTBF:

Backlights min. 50000h

Mechanical dimension:

Case: 307 x 225 x 65)mm

Frontpanel: 315 x 235 x 3mm

cutout: min 301 x 220 mm

Material:

Frontpanel: aluminium powder-coated black

Protective glass

Environmental conditions:

Operating temperature 0-50°C

Storage temperature 0-65°C

Humidity: 10 - 80 % rel. humidity, not condensing

Protection class:

Front IP 65

Norms

EN55022 EN55024 EN61010-1

Part number

10030872 SEM12-F-Deckel multiform 3