


SEM15-FP Mikron

TFT-Replacement 15" for BC110/110B



Overview

- 15 " TFT / LCD Monitor for Heidenhain/ Mikron
- Replacement for 15" CRT-monitor BC110/110B (MC14018U-780B)
- connector and signal timing compatible to the control
- settings via on-screen-menu
- long-term availability
- frontpanel with mounting holes

Description

The monitors SEM15-F are used as Replacement for 14"/15" CRT-monitors BC110/110B in controls TNC-426, TNC-430 from Heidenhain e.g. in Mikron-maschinen UME-600 and UCP-1000. The default timing is compatible to the control, this means after connecting the monitor the visualisation works correctly. Further adjustments can be made via on-screen-menu. The monitor is delivered with protection glass to provide IP65. Fast and simple replacement through mounting holes compatible to original monitor..

Technical Data

Overview:

Industrial TFT Monitor 15" for Heidenhain

Control:

Heidenhain TNC-426/ TNC430

original monitor:

14"CRT-monitor (MC14018U-450B)

Interfaces:

HD-SUB15 / 15-pin 3-row

Synchronisation / Timings:

compatible

Resolution:

max. 1024x768

Visible Picture:

304x228mm

Adjustments:

via on-screen-menu

Brightness / Contrast:

min. 400 cd/qm, 500:1

Power supply:

90-260VAC

MTBF:

Backlights min. 50000h

Mechanical dimensions:

frontpanel (400x320x3 mm); mounting holes compatible to the original monitor

Material:

Frontpanel: aluminium powder-coated black, Protective glass

Environmental conditions:

Operating temperature 0-50°C

Storage temperature 0-65°C

Humidity: 10 - 80 % rel. humidity, not condensing

Protection class:

Front IP 65

Norms:

EN55022 EN55024 EN61010-1

Part number

10030908 SEM15-F-Heidenhain-BC110/110B